

Water Utilities - Flow Measurement Flowmaster 250

Portable Flow & **Pressure Test Instrument**

The Flowmaster 250 measures the flow rate and the pressure at every water drawing off point.

Application

Testing

- Minimum Night Flow Measurement
- Step Flow Measurement
- Flushing
- Hydrants

Features


- Easy To Use
- Robust No Moving Parts
- Portable, Rechargeable and Connectable anywhere
- Data Logging 5v Pulse Output











Additional Accessories

(surcharge)



Technical Data Flowmaster DIGITAL Flow

(EN ISO 12100-1, EN ISO 12100-2, EN 60204)

Battery power supply: rechargeable battery, 10 hours operation, 12 V DC, 2.2 Ah, separate charger included with delivery.

Working temperature: -10 to +50°C.

Connections: B.S. Instantaneous couplings.

Dimensions: 210 mm height, 240 mm width, 390 mm depth.

Weight: 12.5 kg Housing: Aluminium.

Colour: Red.

Flow Meter:

Type: Electromagnetic.

Operating range: 30-3000 L/min.

Accuracy: 30 to 750 L/min \pm 15 L/min, >750 L/min \pm 2%.

Standard functions: Display of current flow rate, display of volume. LCD display: 4-digit, character size 18 mm, background illumination.

Pressure Gauge:

Operating pressure: 0 - 16 bar $\pm 1\%$. Maximum pressure: 25 bar. 63mm diameter.